

EV pedestal charger

DATA SHEET





3 YEAR
PARTS &
LABOUR
GUARANTEE

Get your business electric-ready with the UK's most affordable EV pedestal charger.

With more than 1 in 10 new vehicles being electric, and the number rapidly rising each year, embracing EV has never been more important. Whether it's demand from your tenants, customers, employees, or visitors: the future is definitely electric. Fortunately, we're here to make embracing EV quick and seamless. We'll be with you every step of the way to find the right EV charger for your application. We also provide 48-hour engineer support after installation to give extra peace of mind. Whether it's a car park, public space, workplace, development site or even a theme park – we've got you covered.

Our OCPP compliant pedestal is compatible with any electric vehicle. It can be controlled multiple ways including plug & play, via pay-to-charge solutions* or via our evec app. The charger's integrated LED light also gives users great visibility of the charge point and bays – even on those dark winter nights. Plus, with next day delivery available on our pedestal range, upgrading has never been quicker.

Available in 1-way or 2-way versions and up to 22kW superfast charging.

*pay-to-charge is powered by Monta.

Product features

- Plug and Charge or Mobile app controlled charging
- 4G / Wi-Fi / Ethernet connectivity
- Built-in over current and 6mA DC leakage protection
- Built in Single and Three Phase PEN protection
- OCPP 1.6J SON Compliant
- Over the air updates
- Available as 7.4kW or 22kW
- 48 hour on site engineer support as part of standard warranty
- Next Day Delivery on all units



Superfast charging

Our Pedestal Charger supports charging speeds of up to 22kW, ensuring efficient fast charging for all EVs and PHEVs.



Easy to use

Control your charger easily via our mobile app, plug & charge or via our approved pay-to-charge partner, Monta.



OZEV approved

Secure a grant of up to £14,000 (£350 per socket) for up to 40 charge points with the OZEV workplace charging scheme.



Safe

Our chargers include PEN protection, security breach notifications, and over-the-air updates, ensuring comprehensive security and convenience.



Customisable

Personalise your pedestal with our custom branding service, allowing you to make it uniquely yours.



Speedy delivery

Quickly set up your charging solution with our next-day delivery service available for our entire range of chargers.

	Model: EDP01	Model: EDP02
Item	2x7.4KW Sockets	2x22KW Sockets
Input		
Power Supply	1P+N+PE	3P+N+PE
Rated Voltage	AC220 ~ 240V	AC380 ~ 450V
Rated Current	2x32A(16A ,13A,10A Adjustable)	2x32A(16A ,13A,10A Adjustable)
Output		
Output Voltage	AC220 ~ 240V	AC380 ~ 450V
Maximum Current	2x32A(16A ,13A,10A Adjustable)	2x32A(16A ,13A,10A Adjustable)
Rated Power	2x7.4KW(MAX)	2x22KW(MAX)
User Interface		
Charger Connector	Type 2 sockets	Type 2 sockets
Cable length	N/A	N/A
Material	Galvanized sheet powder-coated metal housing	Galvanized sheet powder-coated metal housing
Colour	Black	Black
Three colour LED	•	•
OLED	•	•
Start mode	•	•
Plug and charge	•	•
OCPP1.6 Ethernet	•	•
evcc app	Optional	Optional
Safety		
Ingress Protection	IP54	IP54
Impact Protection	•	•
Over Current Protection	•	•
Residual Current Protection (AC30mA,DC6mA)	•	•
PEN Protection	•	•
Over/Under Voltage Protection	•	•
Over Temperature	•	•
Certification	CE / UKCA	CE / UKCA
Certification Standard	EN IEC 61851, EN 62196	EN IEC 61851, EN 62196
Environment		
Installation	Floor mounted	Floor mounted
Mounting Options	Ground bases available	Ground bases available
Work Temperature	-25°C ~ 50°C	-25°C ~ 50°C
Work Humidity	3% ~ 95%	3% ~ 95%
Work Altitude	<2000m	<2000m
Package		
Production Dims (H*W*D)mm	1200*250*250	1200*250*250
Package Dims (L*W*H)mm	/	/
Net weight (kg)	/	/
Gross weight (kg)	/	/

	Model: ESP01	Model: ESP02
Item	1x7.4KW Sockets	1x22KW Sockets
Input		
Power Supply	1P+N+PE	3P+N+PE
Rated Voltage	AC220 ~ 240V	AC380 ~ 450V
Rated Current	1x32A(16A ,13A,10A Adjustable)	1x32A(16A ,13A,10A Adjustable)
Output		
Output Voltage	AC220 ~ 240V	AC380 ~ 450V
Maximum Current	1x32A(16A ,13A,10A Adjustable)	1x32A(16A ,13A,10A Adjustable)
Rated Power	1x7.4KW(MAX)	1x22KW(MAX)
User Interface		
Charger Connector	Type 2 socket	Type 2 socket
Cable length	N/A	N/A
Material	Galvanized sheet powder-coated metal housing	Galvanized sheet powder-coated metal housing
Colour	Black	Black
Three colour LED	•	•
OLED	•	•
Start mode	•	•
Plug and charge	•	•
OCPP1.6 Ethernet	•	•
evec app	Optional	Optional
Safety		
Ingress Protection	IP54	IP54
Impact Protection	•	•
Over Current Protection	•	•
Residual Current Protection (AC30mA,DC6mA)	•	•
PEN Protection	•	•
Surge Protection	•	•
Over/Under Voltage Protection	•	•
Over Temperature	•	•
Certification	CE / UKCA	CE / UKCA
Certification Standard	EN IEC 61851, EN 62196	EN IEC 61851, EN 62196
Environment		
Installation	Floor mounted	Floor mounted
Mounting Options	Ground bases available	Ground bases available
Work Temperature	-25°C ~ 50°C	-25°C ~ 50°C
Work Humidity	3% ~ 95%	3% ~ 95%
Work Altitude	<2000m	<2000m
Package		
Production Dims (H*W*D)mm	1200*250*250	1200*250*250
Package Dims (L*W*H)mm	/	/
Net weight (kg)	/	/
Gross weight (kg)	/	/

You may also like...

Meet our **wall mounted** range of commercial chargers. Available up to 22kW.

Explore now at [evec.co.uk/commercial-chargers](https://www.evec.co.uk/commercial-chargers)



VEEC02 Untethered 22kW EV Charger

- ✓ Compatible with Type 1 & Type 2 EVs
- ✓ Tough & Durable
- ✓ Easy to setup and control via the evec app



VEEC04 Tethered 22kW EV Charger

- ✓ Superfast charging
- ✓ Tough & Durable
- ✓ Easy to setup and control via the evec app



www.evec.co.uk/pedestal-charger

0161 2496 780
sales@evec.co.uk

8 Coronet Way, Salford
Manchester, M50 1RE

